

```
tank/home/ahrens@wednesday
tank/home/ahrens@thursday
# zfs rollback -r tank/home/ahrens@tuesday
```

In the above example, the wednesday and thursday snapshots are removed because you rolled back to the previous tuesday snapshot.

```
# zfs list -r -t snapshot -o name,creation tank/home/ahrens
```

| NAME                     | CREATION              |
|--------------------------|-----------------------|
| tank/home/ahrens@tuesday | Wed Aug 27 16:35 2008 |

#### 4.9.7 Overview of ZFS clones

A clone is a writable volume or file system whose initial contents are the same as the dataset from which it was created. As with snapshots, creating a clone is nearly instantaneous, and initially consumes no additional disk space. In addition, you can snapshot a clone.

Clones can only be created from a snapshot. When

a snapshot is cloned, an implicit dependency is created between the clone and snapshot. Even though the clone is created somewhere else in the dataset hierarchy, the original snapshot cannot be destroyed as long as the clone exists. The origin property exposes this dependency, and the **zfs destroy** command lists any such dependencies, if they exist. Clones do not inherit the properties of

the dataset from which it was created. Use the **zfs get** and **zfs set** commands to view and change the properties of a cloned dataset. Because a clone initially shares all its disk space with the original snapshot, its used property is initially zero. As changes are made to the clone, it uses more space. The used property of the original snapshot does not consider the disk space consumed by the clone.

#### OpenSolaris Community

ZFS is open source software. If you want to be a part of ZFS Project and contribute then visit <http://tr.im/zfscommunity>

#### 4.9.8 Creating and destroying ZFS clone

To create a clone, use the **zfs clone** command, specifying the snapshot from which to create the clone, and the name of the new file system or volume. The new file system or volume can be located anywhere in the ZFS hierarchy. The type of the new dataset (for example, file system or volume) is the same type as the snapshot from which the clone was created. You cannot create a clone of a file system in a pool that is different from where the