

original file system snapshot resides.

In the following example, a new clone named `tank/home/ahrens/bug123` with the same initial contents as the snapshot `tank/ws/gate@yesterday` is created.

```
# zfs snapshot tank/ws/gate@yesterday
# zfs clone tank/ws/gate@yesterday tank/home/ahrens/bug123
```

In the following example, a cloned workspace is created from the `projects/newproject@today` snapshot for a temporary user as `projects/teamA/tempuser`. Then, properties are set on the cloned workspace.

```
# zfs snapshot projects/newproject@today
# zfs clone projects/newproject@today projects/teamA/tempuser
```

```
# zfs set sharenfs=on projects/teamA/tempuser
```

```
# zfs set quota=5G projects/teamA/tempuser
```

A clone can be destroyed by `zfs destroy` command.

```
# zfs destroy tank/home/ahrens/bug123
```

Clones must be destroyed before the parent snapshot can be destroyed.

4.9.9 Replacing a ZFS file system with a ZFS clone

You can use the `zfs promote` command to replace an active ZFS file system with a clone of that file system. This feature facilitates the ability to clone and replace file systems so that the origin file system becomes the clone of the specified file system. In addition, this feature makes it possible to destroy the file system from which the clone was originally created. Without clone promotion, you cannot destroy an origin file system of active clones.

In the following example, the `tank/test/productA` file system is cloned and then the clone file system, `tank/test/productAbeta`, becomes the `tank/test/productA` file system.

```
# zfs create tank/test
# zfs create tank/test/productA
# zfs snapshot tank/test/productA@today
# zfs clone tank/test/productA@today tank/test/
```

Geek Hunt Contest

There are questions based on ZFS in the OpenSolaris Geek Hunt Contest at <http://www.thinkdigit.com/opensolaris>. Answer them and others to win an Acer Netbook!