

```
productAbeta
```

```
# zfs list -r tank/test
```

NAME	USED	AVAIL	REFER	MOUNTPOINT
tank/test			314K	8.24G 25.5K /tank/

```
test
```

tank/test/productA	288K	8.24G	288K	/tank/
--------------------	------	-------	------	--------

```
test/productA
```

tank/test/productA@today	0	-		
--------------------------	---	---	--	--

```
288K -
```

tank/test/productAbeta	0	8.24G	288K	/
------------------------	---	-------	------	---

```
tank/test/productAbeta
```

```
# zfs promote tank/test/productAbeta
```

```
# zfs list -r tank/test
```

NAME	USED	AVAIL	REFER	MOUNTPOINT
tank/test			316K	8.24G 27.5K / t a n k /

```
test
```

tank/test/productA	0	8.24G	288K	/
--------------------	---	-------	------	---

```
tank/test/productA
```

tank/test/productAbeta	288K	8.24G	288K	/tank/test/
------------------------	------	-------	------	-------------

```
productAbeta
```

tank/test/productAbeta@today	0	-	288K	-
------------------------------	---	---	------	---

In the above `zfs list` output, you can see that the space accounting of the original `productA` file system has been replaced with the `productAbeta` file system.

Complete the clone replacement process by renaming the file systems. For example:

```
# zfs rename tank/test/productA tank/test/
```

```
productAlegacy
```

```
# zfs rename tank/test/productAbeta tank/test/productA
```

```
# zfs list -r tank/test
```

NAME	USED	AVAIL	REFER
------	------	-------	-------

```
MOUNTPOINT
```

tank/test	316K	8.24G	27.5K / t a n k /
-----------	------	-------	-------------------

```
test
```

tank/test/productA	288K	8.24G	288K / t a n k /
--------------------	------	-------	------------------

```
test/productA
```

tank/test/productA@today	0	-	288K -
--------------------------	---	---	--------

tank/test/productAlegacy0	8.24G	288K	/tank/
---------------------------	-------	------	--------