

```
no changes found
```

Otherwise, you'll get output informing you of the number of changesets involved:

```
$ hg pull
pulling from ssh://anon@hg.opensolaris.org/hg/onnv/
onnv-gate
searching for changes
adding changesets
adding manifests
adding file changes
added 503 changesets with 5608 changes to 4444 files
(run 'hg update' to get a working copy)
$ hg update
4433 files updated, 0 files merged, 376 files removed,
0 files unresolved
```

8.1.3 Using hg bundles of the ON repository

OpenSolaris mercurial repositories are sometimes provided as "bundles" with a .hg extension. There are two types of bundles - Changesets and Incremental. Changeset bundles are complete standalone bundles. To get a working copy of this bundle, download it from the [opensolaris.org](http://opensolaris.org/downloads) downloads page and do the following steps.

```
cd /export/work
hg init
hg unbundle {path}/on-hg-bundle-YYYYMMDD.hg
hg update
```

Incremental bundles are typically named as "on-hg-bundle_yyyymmdd-YYYYMMDD.hg" and contain only incremental changes. They can only be applied to a working copy which contains all changesets up to yyyymmdd and no more. This is verified before the unbundling process by checking the parent property (hg parent) of the bundle. You can apply an incremental bundle to a working copy using the following commands:

```
cd /export/work
hg unbundle on-hg-bundle_yyyymmdd-YYYYMMDD.hg
```