

for text that matches a specified pattern. It can even pass on the processed result to another program, file, or the command line itself.

### 9.4.7 shutdown

Using shutdown command from the Terminal has several advantages. You can control when the shutdown occurs, using these flags:

- Now. You can safely shut down right now by typing `shutdown now`.
- `-h`. Typing `sudo shutdown -h 2235`, will shut down your machine at 10:35 p.m. today
- To make the machine shut down at 4:30 p.m. on January 5, 2009, you should type `sudo shutdown 0901051630`. That number code is in Year[last two digits]MonthDateHourMinute format.
- `-r` flag lets you restart instead of just shutting down as in `sudo shutdown -r now`.

You can even turn off your Macs by remote control, either from across the network or across the world via Internet using telnet or SSH to issue the command.

#### Note

Unless you also use `sudo`, you can only kill programs that you have ownership privileges over. Also if you are having trouble killing an application, you can use the `-9` flag which is the non-catchable, non-ignorable kill.

## 9.5 Enabling the Root Account

Only one person is allowed to browse any Mac OS X directory, unfettered and unrestricted: whoever holds the root (superuser) account.

To enable the root account in Terminal, all you have to do is make up a password for the dormant root account using the `passwd` command.

### `sudo passwd root`

The `passwd` utility will then prompt you to enter a new password for the root account.

Once the root account has a password, you can use it to log in with the user name root. When you do, you'll realise that the root account's Home folder isn't in the Users folder like everyone else's; instead, it's in the private `var` folder. You will also have complete freedom to modify, move, or change the access privileges for any file and folder on your system. 