

```
$time = $facebook->api_client->data_defineObjectProperty("wallpost", "timePosted", 2);  
$post = $facebook->api_client->data_defineObjectProperty("wallpost", "post", 3);  
?>
```

This code snippet is analogous to the SQL:

```
CREATE TABLE wallpost(  
  uid integer,  
  timePosted timestamp,  
  post text  
)
```

It takes a little bit to get used to the DataStore API because you're not performing typical SQL DDL; but once you get yourself around creating the objects, it becomes relatively trivial to use the API as the persistence layer for your application. This API is a boost for those who choose to have Facebook manage their data instead of writing their own SQL queries and using the client library to manage data.

Events API

Facebook has rich event system, which allows users to create events with built-in RSVP features, event-specific media, and export capabilities. The events API allows applications to manage events on its users' behalf with two main wrappers to retrieve information on events. **facebook.events.get** method returns a response based on the filters passed to it and the **facebook.events.getMembers** method returns the RSVP status for Facebook members for a given event. These methods requires extra permissions from the user.

FBML API

The FBML API is a set methods that allow developers to create custom FBML tags, refresh cached images, upload localized strings for internationalisation, and do high-performance updates of cached profile box FBML. The **facebook.fbml.refreshImgSrc** method is used to fetch and catch an image at a given URL. The **facebook.fbml.refreshRefUrl** method is used to refresh content from a given URL and the **facebook.fbml.setRefHandles** method is used to get content as a handle in FBML. You can even register custom FBML tags with Facebook and make them public so that other developers can use them in their own applications.