

API, FQL, mock Ajax, and FBML. Create an index.php file in the Facebook folder of your web server and use the following source code:

```
<?php
$facebook_config['debug'] = false;
$facebook_config['secret_key'] = '<secret key>';
$facebook_config['api_key'] = '<api key>';
require_once('<client library>/facebook.php');
$facebook = new Facebook($facebook_config['api_key'],
$facebook_config['secret']);
$user = $facebook->require_login();
?>
```

This sets up the constants (api_key and secret_key) and instantiates a Facebook object (which includes an instance of the API REST client). To add functionality to the application, use the following code block:

```
<div style="padding:5px;">
<h1>Hello
<fb:name uid="<?=$user?>" firstnameonly="true"
capitalize="true" />
</h1>
<p>What's your new status?</p>
<form>
<input type="text" name="status" value="confused" />
<input type="submit"
clickrewriteid="curr_status"
clickrewriteurl="<callback url>" />
</form>
<div id="curr_status"></div>
</div>
```

The user variable you set in the PHP code is used to display the user name. We've also created a mock Ajax call to populate the empty preview div. Code to handle updating the status goes like:

```
if(isset($_REQUEST['status']))
{
$has_permission =
$facebook->api_client->call_method("facebook.users.
hasAppPermission",
array("ext_perm"=>"status_update"));
if($has_permission){
```