

5.6 Forms

FBML has several tags which facilitate working with form information and perform some common tasks:

- `<fb:request-form>` to create a form for sending requests. You can let your users send requests to add the application (when used with the `<fb:multi-friendselector>` tag). This tag is invalid when working with iframes.
- `<fb:request-form-submit>` to create a submit button for use with the `<fb:request-form>` tag.
- `<fb:multi-friend-input>` to render a multifriend input field like the one used in the message composer.
- `<fb:friend-selector>` to render an autocomplete input box of the user's friends.
- `<fb:submit>` to create a JavaScript submit button for your forms. If you want to use an image instead of a submit button, you can use this like
- `<fb:submit></fb:submit>`.

5.7 Others

FBML has a set of tags that help you build some very useful portions of your application:

- `<fb:comments>` to add comments to an application. You can post and redraw pages that are posted to for a given UID.
- `<fb:google-analytics>` to add JavaScript to your application so you can use Google Analytics to track your application usage.
- `<fb:mobile>` to displays content for mobile users (<http://m.facebook.com>). Content not enclosed within this tags will be ignored for mobile users.
- `<fb:random>` to randomly rotates certain parts of your application content (for quotes, pictures, or even advertising). This tag randomly choose an element from within the tag (defined by the `<fb:random-option>` tag) and also allows you to weight these options to appear more often (or less often) than other options.
- `<fb:js-string>` define a string to reference later in FBJS.
- `<fb:fbml>` define the version of FBML you wish to use.
- `<fb:fbmlversion>` to display the version of FBML that is currently being used.
- `<fb:redirect>` to redirect the browser to another URL in your application.
- `<fb:ref>` define FBML that resides at a URL that you then call later