

```
</div>
```

If it's an IFrame, add the following line for the new info button placeholder `<div>` after the add button placeholder `<div>` in `index_iframe.php`:

```
<div id='infobutton'></div>
```

Also, add this line right after the `showAddSectionButton()` call for the Profile button in `index_iframe.php`:

```
FB.Connect.showAddSectionButton('info', document.  
getElementById('infobutton'));
```

Finally, you need to add the following line to `main.css` to position the button in the banner:

```
#infobutton { position:absolute; top:48px; right:33px; }
```

7.7 Managing the FBML Cache

FBML for profile boxes are cached. This works fine with applications with completely static content. But you might want to update a user's profile boxes when he/she accesses the application to reflect the most current information. If you want to update many of your users' profile boxes at once because of a general style change or content change that applies to a large set of users, you can simply set up a server-side cron job to iterate through all the application's users and call `profile.setFBML()` for them. However, if your application has a large number of users, this can take forever to accomplish, and be unmanageable. For this very reason, Facebook provides you the `<fb:ref>` FBML tag can mark blocks of FBML that can be updated across many profiles with a single call. There are two ways in which you can use this tag: by URL and by Handle. They both eventually achieve the same result, but one might fit better with your application design than the other. If you specify a URL, Facebook calls that URL to get the new content when the cache is being refreshed, while if you specify a Handle, your application directly passes the new FBML content. The `<fb:ref>` tags can also be nested, but only the content of the Handle or URL specified is updated.

Let us see how an application might use `<fb:ref>` with a Handle. Create a block of FBML and pass it to `fbml.setRefHandle()` with a unique Handle identifier. Then, use `<fb:ref handle='youridentifier' />` in your profile FBML content wherever you want that block of FBML to appear and pass it to `profile.setFBML()`. After this, your application can just call `fbml.setRefHandle()` with new FBML to update all profiles that contain that Handle to use the new content. Only the section in the Handle will be updated.