

```

action="invitation processor page"
method="POST"
invite="true"
type="Application Name"
content="Content of your Mail">
<fb:multi-friend-selector
showborder="false"
actiontext="Invite friends to the Application Name"
exclude_ids="exclude friends who are already using
this app"
max="20" />
</fb:request-form>

```

The various parameters for this FBML tag are:

- **Action** - This parameter supplies the information as to where the page will submit all the information when someone clicks on the send invitation or skip button.
- **Method** - This parameter is used to select GET or POST, the way information will be submitted.
- **Invite** - It can be true or false. When set as true, the invitation will go as invitation, otherwise it will go as a request. This change actually reflects the content of the invitation that the user will get.
- **Type** - This one is used to reflect the context of your application. It is usually set the same as the application name.

9.1.2 fb:req-choice

This tag is used to insert a button in your request message, and define the name and target URL. So when a user receives your invitation, they will also see this button, and when they click on it, they will be redirected to the URL that you have specified. This is very useful if you want them to install the application, just by providing a nice button inside your invitation message.

The various parameters for this FBML tag are:

- **url** - This is the target URL which used to redirect the user on a click event.
- **Label** - This is just the caption for the button.

Example:

```

<fb:req-choice url="http://apps.facebook.com/example/
Accept.php" label="Accept" />

```

Don't use "ignore" as the caption of any request button because it is there