

by default. So if you insert another ignore button, the code will not work and you might lose all the other buttons inside too.

9.1.3 fb:request-form-submit

This tag is used to display a submit button inside your invitation form. The various parameters for this FBML tag which let you display the user's name or the full name inside this button are:

- **uid** - The user id of the user you want to send this invitation to.
- **label** - Used to provide a caption to the button. Tip -To show the first name of the user, use %n and to show the full name, use %N.

Example:

```
<fb:request-form-submituid= 'some uid' label= 'send %N an Invitation' />
```

9.1.4 fb:multi-friend-selector

This FBML tag is used to draw a friend selector widget anywhere in your canvas page. The various parameters for this FBML tag are:

- **actiontext** -Used to specify what to display at the top of this friend selector as the heading.
- **showborder** - Can be set to true or false.
- **rows** - Used to specify the number of rows, that friends will be shown in. The default value is 5. But you can choose anything from 3 to 10.
- **max** - Used to specify the maximum number of friends a user can select at a time to send an invitation to. It is advisable to keep it at 20 because of Facebook regulations.
- **exclude_ids** - This is a comma separated list of friends who are not to be shown inside this selector object. Use this to exclude all your friends who have already installed this application.
- **bypass** - Used to add a label to the skip button.
- **condensed** - If set to true, it will create a condensed page that looks far different from a full version.

9.1.5 fb:multi-friend-input

Instead of using a multi-friend selector in your Invitation system, you can also use a multi-friend input in a fb:request-form, although it is much less user-friendly as compared to a friend selector. The usage of multi-friend selector is very simple and you can select an arbitrary numbers of friends.

The various parameters for this FBML tag are: