

```
URLWithString:emailString]];
    [emailString release];
}
-(IBAction) btnSend: (id) sender{
    [self sendEmailTo:to.text withSubject:subject.text
withBody:body.text];
}
- (void)dealloc {
    [to release];
    [subject release];
    [body release];
    [super dealloc];
}
```

Save the project and press [command] + [R] to start the application on the iPhone Simulator. Now you will be presented with the interface you just created. Once you enter in all the relevant fields and click on SendEmail, the Mail application will be invoked with all the fields filled just as you did in your application by default. All you need to do now, is click on the Send button in Mail and you are done.

Accessing Safari

To invoke the default web browser of the iPhone, i.e., Safari from your application, you need to use the following code with the URL as per your preference. You can even take the URL from a text field entered by an user:

```
[[UIApplication sharedApplication] openURL:[NSURL
URLWithString: @"http://www.thinkdigit.com"]];
```

Accessing the Dialer

To make a phone call to a number specified by your application, you can invoke the iPhone's dialer with the number prefilled from within your application using the following source code:

```
[[UIApplication sharedApplication] openURL:[NSURL URLWi
thString:@"tel:9881xx3xxx"]];
```

Accessing SMS

To send an SMS using the SMS application on the iPhone with a prefilled number, you can invoke it from your application using the following source code: