

Create a new View-based Application project in Xcode. We will name it MotionDetection. Next open the MotionDetectionViewController.xib in the InterfaceBuilder by double-clicking on it and then populate the View window with 6 labels to test the X, Y and Z values.

Then Edit the MotionDetectionViewController.h file with the following source code:

```
#import <UIKit/UIKit.h>

@interface MotionDetectionViewController :
    UIViewController
<UIAccelerometerDelegate> {
    IBOutlet UILabel *labelX;
    IBOutlet UILabel *labelY;
    IBOutlet UILabel *labelZ;
}
@property (nonatomic, retain) UILabel *labelX;
@property (nonatomic, retain) UILabel *labelY;
@property (nonatomic, retain) UILabel *labelZ;
@end
```

After this, go back to the Interface builder and control click and drag the File Owner's item to each of the three label views that you decide to detect values and select labelX, labelY and labelZ. After this you are ready to write the actual code to test the values in the MotionDetectionViewController.m file:

```
#import "MotionDetectionViewController.h"
@implementation MotionDetectionViewController
@synthesize labelX, labelY, labelZ;
- (void)viewDidLoad {
    UIAccelerometer *acc = [UIAccelerometer
sharedAccelerometer];
    acc.delegate = self;
    acc.updateInterval = 1.0f/60.0f;
    [super viewDidLoad];
}
- (void)accelerometer:(UIAccelerometer *) acc
didAccelerate:(UIAcceleration *)acceleration {
    NSString *str = [[NSString alloc] initWithFormat:@"%g",
acceleration.x];
    labelX.text = str;
```