

```

    str = [[NSString alloc] initWithFormat:@"%g",
acceleration.y];
    labelY.text = str;
    str = [[NSString alloc] initWithFormat:@"%g",
acceleration.z];
    labelZ.text = str;
    [str release];
}
- (void)dealloc {
[labelX release];
[labelY release];
[labelZ release];
[super dealloc];
}

```

Save the project and press [command] + [R] to start the application on the iPhone Simulator. The labels will now show real time orientation values of the X,Y and Z axes. So in concept, you know how to use them. Next is the part of writing algorithms in your application to use these. But we will leave that to your creativity.

We will however, explain how to detect shakes using the Shakes API. Again, create a new View-based Application project in Xcode. We will name it ShakeDetect. Open the ShakeDetectViewController.xib in the Interface Builder by double-clicking on it and populate the View window with a Text Field and a DatePicker view. Then open the ShakeDetectViewController.h file and write in the following source code:

```

#import <UIKit/UIKit.h>

@interface ShakeDetectViewController : UIViewController
{
    IBOutlet UITextField *textField;
    IBOutlet UIDatePicker *datePicker;
}
@property (nonatomic, retain) UITextField
*textField;
@property (nonatomic, retain) UIDatePicker
*datePicker;
-(IBAction) doneEditing: (id) sender;
@end

```

After this, you need to go back to the Interface Builder and control-