

```
[latitudeTextField release];  
[longitudeTextField release];  
[accuracyTextField release];  
[super dealloc];  
}
```

Save the project and press **[command] + R** to start the application on the iPhone Simulator. This will show you the location of the place that the Simulator has locked the GPS on to. To test it in a real world scenario, you need to try this on a real iPhone.

Now that you can obtain the values of the position that you are at, it would be interesting to use this with the MapKit API to open the Google Map in your application with that location as the destination. Lets see how to go about it.

We will use the same project we created last. Just add a Button view to the View window in the UsingGPSViewController.xib file and add the MapKit framework in the same way that you added the CoreLocation framework. Then edit the UsingGPSViewController.h file to:

```
#import <UIKit/UIKit.h>  
#import <CoreLocation/CoreLocation.h>  
#import <MapKit/MapKit.h>  
@interface UsingGPSViewController : UIViewController  
    <CLLocationManagerDelegate> {  
    IBOutlet UITextField *accuracyTextField;  
    IBOutlet UITextField *latitudeTextField;  
    IBOutlet UITextField *longitudeTextField;  
    CLLocationManager *lm;  
    MKMapView *mapView;  
    }  
@property (retain, nonatomic) UITextField  
    *accuracyTextField;  
@property (retain, nonatomic) UITextField  
    *latitudeTextField;  
@property (retain, nonatomic) UITextField  
    *longitudeTextField;  
-(IBAction) btnViewMap: (id) sender;  
@end
```

Next, go back to the Interface builder and Control-click + drag the Button view to the File Owner's item and select btnViewMap. Also, edit the