

UsingGPSViewController.m file to handle the event:

```
-(IBAction) btnViewMap: (id) sender {
    [self.view addSubview:mapView];
}

- (void) viewDidLoad {
    lm = [[CLLocationManager alloc] init];
    lm.delegate = self;
    lm.desiredAccuracy = kCLLocationAccuracyBest;
    lm.distanceFilter = 1000.0f;
    [lm startUpdatingLocation];
    mapView = [[MKMapView alloc] initWithFrame:self.view.
bounds];
    mapView.mapType = MKMapTypeHybrid;
}

- (void) locationManager: (CLLocationManager *)
manager didUpdateToLocation: (CLLocation *) newLocation
fromLocation: (CLLocation *) oldLocation{
    NSString *lat = [[NSString alloc] initWithFormat:@"%g",
newLocation.coordinate.latitude];
    latitudeTextField.text = lat;
    NSString *lng = [[NSString alloc] initWithFormat:@"%g",
newLocation.coordinate.longitude];
    longitudeTextField.text = lng;
    NSString *acc = [[NSString alloc] initWithFormat:@"%g",
newLocation.horizontalAccuracy];
    accuracyTextField.text = acc;
    [acc release];
    [lat release];
    [lng release];
    MKCoordinateSpan span;
    span.latitudeDelta=.005;
    span.longitudeDelta=.005;
    MKCoordinateRegion region;
    region.center = newLocation.coordinate;
    region.span=span;
    [mapView setRegion:region animated:TRUE];
}

- (void) dealloc{
```