

you will have to modify the attribute of the label, that can be done as explained above, by opening the **Tools > Size Inspector**. Here, alter the “Autosizing” attribute. You can also anchor your visual object to any of the screen edges.

1.3 Creating actions

Now it's time to get back to writing some code. Let us try and do something on our screen when you click on a button in your UI. For this we will first create an action and then link that action to the click of the window.

So gear up and focus back on the tiny window called the “digitViewController.xib” this will be one of the three windows in your interface builder. This contains only three things inside it namely

- File's Owner
- First Responder
- View

Now select File's Owner and then open the Identity Inspector from the tools menu. Add a Class Action and name it **bnClicked:**, this has created a class action called **bnClicked:.** Don't miss out on the colon at the end.

Now drag the button from the “View” window to the “File's Owner” in the **digitViewController.xib**; this should result in a pop-up containing the **bnClicked:** action that you just created. This links the click of the button with that action.

Now to actually do some action, you will have to write its required code, this can be done by editing two files. The first being **DigitViewController.h** where you would add a header declaration for the **bnClicked:**

It should resemble something like this:

```
// digitViewController.h
// Created by Subiet
// Created cause he was bored
```

```
#import < UIKit/UIKit.h >
@interface digitViewController : UIViewController {
}
-(IBAction) bnClicked:(id)sender;
@end
```

The line in bold, is your declaration. Now move towards the **DigitViewController.m** file, this is where you would write the actual action code:

```
- (void)dealloc {
```