

You need to declare all the classes in the header file (.h) without any implementation defined. This code essentially declares a class named `BasicClass`, and this class inherits from the base class named `NSObject`, which is the root class of most Objective-C classes. It defines the basic interface of a class in Objective-C and contains methods common to all classes that inherit from it. It also provides the standard memory management and initialization framework used by most objects in Objective-C as well as reflection and type operations.

If otherwise that class we wanted to declare was a View Controller class, we will inherit from the `UIViewController` class:

```
@interface BasicClassViewController : UIViewController
{
}
```

Initializers

While creating an instance of a class, you can also initialise it at the same time. For example, in the running example that we've been using, you had this statement:

```
BasicClass *sc = [[BasicClass alloc] init];
```

We use the `alloc` keyword here to allocate memory for the object, and when an object is returned, we call the `init` method on the object to initialise the object. We've however not defined a method named `init` in our `BasicClass`. But this `init` method automatically comes from the `NSObject` class, which we've told you is the base class of most classes in Objective - C. This method is known as an initialiser. You can also create additional initialisers by define other methods that begin with the `init` word.

```
#import <Foundation/Foundation.h>
@class SecondClass;
@interface BasicClass : NSObject {
    SecondClass *secondClass;
    float rate;
    NSString *name;
}
-(void) doSomething;
-(void) doSomething:(NSString *) str;
-(void) doSomething:(NSString *) str
withAnotherPara:(float) value;
+(void) alsoDoSomething;
```