

the code for what you have done in the last two steps, in the pop-up that follows choose merge. This will open a “diff” like window for you where the left part indicates the code generated by Interface Builder for us and the right indicates the pre-existing code.

The DigitViewController.h file should appear as follows

```
#import < UIKit/UIKit.h >
@interface DigitViewController : UIViewController {
    IBOutlet UITextField *nmTextField; // This is the
additional
    // line of code corresponding to the outlet you just
created.
```

```
    // Remember IBOutlet is a reserved keyword
}
```

```
- (IBAction)btnClicked:(id)sender;
```

```
@end
```

We have demonstrated above how to add outlets via the GUI, to do the same thing with code, you can just append a line in the framework generated above. So if you want to add another outlet by the name of lastNmTextField your digitViewController.h will appear as follows:

```
#import < UIKit/UIKit.h >
@interface BasicUIViewController : UIViewController {
    IBOutlet UITextField *nameTextField;
    IBOutlet UITextField *ageTextField;
}
- (IBAction)btnClicked:(id)sender;
@end
```

Now if you check via the GUI by opening the Inspector window for “File’s Owner” you would see your newly added outlet

Now refer to an alternate version of the code we had just written

```
#import < UIKit/UIKit.h >
@interface digitViewController : UIViewController {
    @property (nonatomic, retain) IBOutlet UITextField
    *nameTextField;
}
- (IBAction)btnClicked:(id)sender;
@end
```

Here the member variable has been explicitly exposed as a property using the @property identifier. This is used in combination with the @