

```
@property (nonatomic, retain) UIImageView *imageView2;
@end
```

Now move to your flipViewController.m file and edit it as follows:

```
#import "flipViewController.h"
@implementation flipViewController
@synthesize pageControl;
@synthesize imageView1, imageView2;
(void) viewDidLoad { //Void is the return type
    //Set the first image in imageView1 and load the 2nd
in the tempImage view
    [imageView1 setImage:[UIImage imageNamed:@"1.
jpeg"]];
    tempImageView = imageView2;
    [imageView1 setHidden:NO];
    [imageView2 setHidden:YES]; //Since we don't want
to display the 2nd image yet
    // This following declares the event handler for the page
control
        [pageControl addTarget:self action:@
selector(pageTurning:)
        forControlEvents:UIControlEventValueChanged];
    [super viewDidLoad];
}
- (void) pageTurning: (UIPageControl *) pageController
// To account for a change of page
// Void is the return type for this method
{
    //Declare and interger by the name of next page of type
NSInteger
    // Load the value of the current page in it
    NSInteger nextPage = [pageController currentPage];
    // A very c/c++ similar switch statement using the
"nextPage" variable
    switch (nextPage) {
        case 0:
            [tempImageView setImage:[UIImage
imageNamed:@"1.jpeg"]];
            break;
```