

```
// This is the declaration of an action which accounts
for a change in the segmented control
- (IBAction) segmentChanged:(id)sender {
    // Loads the selectedIndex property of the
    SegmentedControl into a integer variable
    // called the selectedSegment
    NSInteger selectedSegment = segmentedControl.
selectedIndex;
    // Now you can either use a switch case statement as
    demonstrated in the last example
    // But since we are switching only between two different
    views so you can use an if-else ladder
    if (selectedSegment == 0) {
        [self.view1 setHidden:NO]; //Equal to making
the view1 visible
        [self.view2 setHidden:YES];
    }
    else{
        [self.view1 setHidden:YES];
        [self.view2 setHidden:NO];
    }
}
- (void) dealloc {
    [segmentedControl release];
    [view1 release];
    [view2 release];
    [super dealloc];
}
```

Done. Yes, it's that simple. Build and Run your application to test it in the iPhone simulator. In the simulator you can change the view in focus by tapping on the selector bar at the top.

4.3 Multiple Views using Buttons

There may be cases when you want multiple views like the above but don't want them to be displayed all at the same time, or want them to be displayed based on the User Interaction. Consider an example where your main view displays two buttons called "Choice1" and "Choice2". Based on which button your user clicks he is displayed a specific view which has another