

say in a field where you are accepting proper nouns (especially in India). It would be a good idea to switch it off.

Keyboard: There are three major types available apart from default, the email address, Phone Pad, and Number Pad. So in case you are asking for a numeric pin code, it would be advisable to switch to the numeric pad while entering a phone number. It is recommended to switch to the Phone Pad option.

Appearance: Basic appearance characteristics

Return Key: Modify the type and behaviour of your return key. There are lots of options available here like Go, Google, Next, Join, Route, Search, Send, Yahoo and Done.

5.2 Make it vanish

The KeyBoard is auto summoned when any TextField View gets activated. But what if (and this is a common scenario) you want the keypad to go away after a user hits the return key or any of its variation while the TextField is still active. Consider the following: you have asked the user for a search term and set your return key as “search”. Now when the user hits the search button after typing his/her query, the TextField view is still active, but ideally the keypad should disappear. This is exactly what we will learn in this section.

We will continue with the KB application that you had created above. Select the “File’s Owner” icon in the kbViewController.xib window and view its Identity Inspector window. Over here, add a new action by clicking on the “+” icon below the Class Actions section. Let us call it “vanish”.

Now switch to your “View” window and right-click the TextField view in it. This will display the list of possible events in it. Select “Did End on Exit” and then drag it to the “File’s Owner” item. This should give you the pop-up with the “vanish” action that you have just created, select it. This should be enough for the kbViewController.xib file, save and exit it.

Back to your Xcode, modify your kbViewController.h file as follows:

```
#import <UIKit/UIKit.h>
@interface kbViewController : UIViewController {
}
- (IBAction) vanish:(id) sender;
@end
```

Now that you have edited your header file, open your kbViewController.m file:

```
#import "KbViewController.h"
```