

```

<UIApplicationDelegate> {
    UIWindow *window;
    //Note that this time the subclass is called the //
    UINavigationController, unlike any other code we have seen
    before
    UINavigationController *navigationController;
}
@property (nonatomic, retain) IBOutlet UIWindow *window;
@property (nonatomic, retain) IBOutlet
UINavigationController
    *navigationController;

```

As explained in the comment that UINavigationController is a specialized View Controller provided by the SDK for the Menu driver applications.

Now open your NaviAppDelegate.m file

```

#import "NaviAppDelegate.h"
#import "RootViewController.h"
@implementation NaviAppDelegate
@synthesize window;
@synthesize navigationController;
#pragma mark -
#pragma mark Application lifecycle
//The method below makes the view of the Navigation
Controller the //default visible view, as soon as the
application is loaded into //the cpu
- (void)applicationDidFinishLaunching:(UIApplication *)
application {
    [window addSubview:[navigationController view]];
    [window makeKeyAndVisible];
}

```

Since the interface builder section is primarily a GUI area, we open the MainWindow.xib. Here, you'll observe that instead of the blank view window as in a "view-based" application, this view already contains a "Navigations Controller" item. The Navigation Controller item contains within itself a single Navigation Bar as well as a default view from the "RootViewController" class.

Following the visibility of the view from the RootViewController class we open the RootViewController.xib file in the Interface builder. If you look closely at the "RootViewController.xib" window you will notice that it comes