

preloaded with a table view (The table view will be discussed in detail in the next chapter). The table view is not a necessity for the RootViewController.xib file, but it is present so often that the sdk loads it by default.

So say you want to display the name of your friends over here, open up Xcode and start editing the RootViewController.m file:

```
#import "RootViewController.h"
@implementation RootViewController
    NSMutableArray *listOfFriends; //declares an array by
the name of listOfFriends
- (void)viewDidLoad {
    listOfFriends = [[NSMutableArray alloc] init];
    // Now we will populate the array with actual names
    [listOfFriends addObject:@"Friend 1"];
    [listOfFriends addObject:@" Radhika"];
    [listOfFriends addObject:@"John" ];
    [listOfFriends addObject:@"Adi"];
    [listOfFriends addObject:@"Rico"];
    [listOfFriends addObject:@"Marsh"];
    [listOfFriends addObject:@"Some Friend"];
    [listOfFriends addObject:@"Some more friends"];
    [listOfFriends addObject:@"Alien 1"];
    [listOfFriends addObject:@"Alien from Pluto"];
    // The Following variable sets the title of the
navigation bar
    self.navigationItem.title = @"Friends";
    [super viewDidLoad];
}
- (void)dealloc {
    [listOfFriends release];
    [super dealloc];
}
```

Now we need to inform the UI how many items were there in the list and what should be the appearance of each cell this can be done by modifying two methods of the table view. Don't worry if you don't understand some of the code below, as you read the later chapters this will become clear to you.

TableView:numberOfRowsInSection should resemble like this

```
- (NSInteger)tableView:(UITableView *)tableView
    numberOfRowsInSection:(NSInteger)section {
```