

```
#import "WorkOnFilesViewController.h"
@implementation WorkOnFilesViewController
//define the method that returns the path to the
application's Documents directory
-(NSString *) documentsPath {
    NSArray *paths = NSSearchPathForDirectoriesInDomains(
NSDocumentDirectory, NSUserDomainMask, YES);
    //This function creates a list of directory search paths
and indicates that you are looking for //theDocuments
folder. The NSUserDomainMask specifies to search in the
application's //home directory.
    NSString *documentsDir = [paths objectAtIndex:0];
    //This command is used to obtain the path to the
Documents folder, which is the first item //of the array
you created. There is only one Documents folder for each
application.
    return documentsDir;
}
//read content from a specified file path
-(NSString *) readFromFile:(NSString *) fi lePath {
    //check if the file exists
    if ([[NSFileManager defaultManager] fi leExistsAtPath:fi
lePath])
    {
        //read the content of the file into an NSArray
object.
        NSArray *array = [[NSArray alloc] initWithContentsOfFile:
filePath];
        NSString *data = [[NSString alloc] initWithFormat:@"%@",
[array objectAtIndex:0]];
        //We extracted only the first element of the array
because our file //just contains a single line of text.
Account for this in an actual //implementation.
        [array release];
        return data;
    }
    else
        return nil;
}
```