

```

}
//This function creates an NSMutableArray and adds the
text to be written into the specified file //path.
- (void) writeToFile:(NSString *) text
withFileName:(NSString *) filePath {
    NSMutableArray *array = [[NSMutableArray alloc] init];
    [array addObject:text];
    [array writeToFile:filePath atomically:YES];
    //The automatically parameter here indicates that the
file should first be written into a //temporary file, and
then renamed to the file name specified. This guarantees
that the file //is not corrupted in the case that your
iPhone crashes while writing the file.
    [array release];
}
// Implement viewDidLoad to do additional setup like
creating the pathname for the file that you //want to
save, writing a string into that file and then eventually
reading it back and printing it in the //Debugger Console
window after You've loaded the view from the xib.
- (void)viewDidLoad {
    //formulate filename
    NSString *fileName = [[self documentsPath]
stringByAppendingPathComponent:@"digit.txt"];
    //write something to the file
    [self writeToFile:@"Whatever string you want to write"
withFileName:fileName];
    //read it back
    NSString *fileContent = [self readFromFile:fileName];
    //display the content read in the Debugger Console
window
    NSLog(fileContent);
    [super viewDidLoad];
}

```

Save the project and press [command] + [R] to start the application on the iPhone simulator. On the simulator, navigate to the Documents folder of your application from the Finder. You will see that a file called digit.txt is visible. This file will be present inside /private/var/mobile/