

```

imageView.contentMode = UIViewContentModeCenter;
} break;
}
} break;
//double-touch
case 2: {
//get info of first touch
UITouch *touch1 = [[allTouches allObjects]
objectAtIndex:0];
//get info of second touch
UITouch *touch2 = [[allTouches allObjects]
objectAtIndex:1];
//get the points touched
CGPoint touch1PT = [touch1 locationInView:[self view]];
CGPoint touch2PT = [touch2 locationInView:[self view]];
NSLog(@"Touch1: %.0f, %.0f", touch1PT.x, touch1PT.y);
NSLog(@"Touch2: %.0f, %.0f", touch2PT.x, touch2PT.y);
} break;
}
}

```

Save the project and press [command] + [R] to start the application on the iPhone Simulator. In the Simulator, if you press the Option key, two small circles will appear. Clicking on the screen now will simulate two fingers actually touching the screen of the device. You can also click the mouse and move it across to simulate pinching.

9.3 Using the pinch gesture

Pinch gesture involves using two fingers touching the screen and pinching by moving them closer to each other. In general, this translates to a zoom out action in the standard iPhone applications. With use knowing the technique of multi-touches, it should be fairly easy to implement. Use the same project that you created earlier. Open the TouchDetectionViewController.h file and edit it like:

```

#import <UIKit/UIKit.h>

@interface TouchDetectionViewController :
UIViewController {
    IBOutlet UIImageView *imageView;
}

```