

The parameters are as follows:

rtgen hash_algorithm charset plaintext_len_min plaintext_len_max table_index chain_len chain_num part_index

hash_algorithm

The hash algorithm to use for generating the tables md5, ntlm / lm for Windows

charset

The character set for the password. Supported options are:

numeric	0123456789
alpha	ABCDEFGHIJKLMNOPQRSTUVWXYZ
alpha-numeric	ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789
loweralpha	abcdefghijklmnopqrstuvwxyz
loweralpha-numeric	abcdefghijklmnopqrstuvwxyz0123456789
mixalpha	abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ
mixalpha-numeric	abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789
ascii-32-95	!"#\$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{ }~
ascii-32-65-123-4	!"#\$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`{ }~
alpha-numeric-symbol32-space	ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789!@#\$%^&*()-_+=~[]{} \;:'",<.>./

plaintext_len_min plaintext_len_max

These are some of the more obvious parameters. They define the minimum and maximum lengths of the plaintexts for which the password is to be found. So for a length from 1 to 7 there will be no likelihood of there being a hash for a 8 character password, but most combinations within the specified character set will likely be present.

table_index chain_len chain_num part_index

These are the least obvious and most complicated parameters. Since you have some idea of rainbow tables, you will probably know what chain_length means. Hint, it is the number of hash-reduce cycles which form the chain, and lead to the final hash stored for each chain.

The table_index is used to define which reduce function to use for the table and the part_index is for deciding how to generate the initial starting point for the rainbow table.

The settings recommended by the creators of the software for a 99.9% probability of cracking hashes are (for md5):

rtgen md5 loweralpha-numeric 1 7 0 3800 33554432 0