

```

owasp@custom: ~$ strobe 192.168.1.1
strobe 1.05 (c) 1995-1999 Julian Assange <proff@iq.org>.
192.168.1.1 21 ftp File Transfer [Control] [96,38P]
-> 228 Beutel FTP version 1.0 ready at Thu May 13 20:49:02 201
0\r\n
192.168.1.1 23 telnet Telnet [112,38P]
-> \255\251\3\255\251\1\r\n
-> Password:
owasp@custom: ~$

```

Strobe

```

owasp@custom: ~$ nc -v -w2 -z 192.168.1.1 1-100
192.168.1.1: inverse host lookup failed: Unknown host
(UNKNOWN) [192.168.1.1] 80 (www) open
(UNKNOWN) [192.168.1.1] 23 (telnet) open
(UNKNOWN) [192.168.1.1] 21 (ftp) open
owasp@custom: ~$

```

netcat

of software, we can possibly gain control of remote computer.

Enumeration is a rather complex topic, since each different service needs to be coaxed in a different way to give up this information. For each different type of service, whether it is a web server, a mail server, or a VNC server, knowing the application name and version can go a long way towards discovering an exploit. Going into such detail is out of the scope of this book!



SuperScan 4.0

To secure a system from the ill effects of enumeration, one of the most important rules is to shut down any unnecessary services. Find out if the services you want to run can have their banners turned off, so that it is difficult for a hacker to gain information about application version number which can be used to find exploits for the system. Make good use of a firewall letting in only the minimum required.

3.1.5 Penetration

Finally, what we have been waiting for! The actual hacking act. This step involves discovering and exploiting flaws in the applications running on the remote system. How do we do that? Well, using the information