

.php: :\$DATA which it is not configured to process.

Another similar exploit that can affect Windows systems is due to the case-insensitive file system of Windows. Apache on Windows itself is case sensitive, being focused on *NIX platforms. However, it is running on a case-insensitive system.

This vulnerability, called the “CGI Script Source Code Disclosure Vulnerability in Apache for Windows”, retrieved from <http://marc.info/?l=bugtraq&m=115527423727441&w=2> is explained as follows:

ADVISORY NAME:

CGI Script Source Code Disclosure Vulnerability in Apache for Windows

VULNERABLE SYSTEMS:

The vulnerability has been verified on Apache 2.2.2 running on Microsoft Windows XP, Version 2002, Service Pack 2.

FOUND BY:

Susam Pal

FOUND ON:

8th August, 2007

VULNERABILITY TYPE:

Information Disclosure

SYSTEM DESCRIPTION:

Apache HTTPD is a web server that can run on many platforms to provide web-service. The basic server configuration is controlled by the file 'httpd.conf'. The 'DocumentRoot' directive controls which directory is considered to be root for serving documents. For instance:-

```
DocumentRoot "/home/webmaster/site/docroot/"
```

In the above example, a request to 'http://[target]/foo.html' would fetch the 'foo.html' page from '/home/webmaster/site/docroot/' directory of the server.

The 'ScriptAlias' directive controls which directory contains server scripts. The following is an example of a typical 'ScriptAlias' directive:-

```
ScriptAlias /cgi-bin/ "/home/webmaster/site/docroot/cgi-bin"
```

If a user makes a direct request to 'http://[target]/cgi-bin/foo' where 'cgi-