

adduser

The `adduser` command will create a new user. To simply create a new user, type `sudo adduser $loginname`. This will create the user's home directory and default group. It will prompt for a user password and then further details about the user.

passwd

The `passwd` command will change the user's password. If simply run by a regular user, it will change his password. If run using `sudo`, it can change any user's password. For example, `sudo passwd digit` will change Digit's password.

who

The `who` command will tell you who is currently logged into the machine.

addgroup: The `addgroup` command will add a new group. To create a new group, type `sudo addgroup $groupname`.

deluser

The `deluser` command will remove a user from the system. To remove their files and home directory, you need to add the `-remove-home` option

delgroup

The `delgroup` command will remove a group from the system. You cannot remove a group that is the primary group of any users.

Getting Help on the Command Line

This section will provide you with some tips on getting help on the command line. The commands `-help` and `man` are the two most important tools at the command line.

Virtually all commands understand the `-h` (or `-help`) option which will produce a short usage description of the command and its options, then exit back to the command prompt. Try `man -h` or `man -help` to see this in action.

Every command and nearly every application in Linux will have a `man` (manual) file, so finding them is as simple as typing `man` command to bring up a longer manual entry for the specified command. For example, `man mv` will bring up the `mv` (Move) manual.

Some helpful tips for using the `man` command include:

- arrow keys

- Move up and down the man file using the arrow keys.

q

Quit back to the command prompt by typing `[Q]`.