

about running commands as root. This can be useful if there are lots of administrators on a system. However, people usually ignore the warning. The default installation disables the lecture message: `!lecture`.

`timestamp_timeout`

This option lists the number of minutes before `sudo` requires you to re-enter your password. If you are running many `sudo` commands in a row, then it can become very inconvenient to re-enter your password after every command. The default configuration is 15 minutes (`timestamp_timeout=15`)-if your last `sudo` command was executed more than 15 minutes ago, then you will need to re-enter your password to run `sudo`. Setting the value to zero will always prompt for a password; setting the value to a negative number disables the timeout. If you are in a very sensitive environment, then you may want to lower this value (or set it to zero).

`tty_tickets`

If you have lots of windows open, then you will notice that you need to enter your password the first time you run `sudo` in any window. This is due to the `tty_tickets` flag-every terminal (tty) has its own `sudo` environment. If you disable this flag (`!tty_tickets`), then entering your password for `sudo` in one window will stop the `sudo` password prompts in all other windows.

`fqdn`

When host names are used in the `sudoers` file, this flag specifies the use of fully qualified domain names (`fqdns`).

`passwd_tries`

This sets how many password attempts the user gets before `sudo` fails. The default is `passwd_tries=3`.

`insults`

This is a fun flag. If the user enters in a bad password, then `sudo` will generate a random message. (The default is `!insults`.) For example:

```
$ sudo id
Password: [wrong]
Just what do you think you're doing Dave?
Password: [wrong]
It can only be attributed to human error.
Password: [wrong]
My pet ferret can type better than you!
sudo: 3 incorrect password attempts
```