

directory for files that will allow for this type of authenticated SSH access. e.g. `/home/username/.ssh/authorized_keys`.

Remove or rename the directory `.ssh/` in the user's home folder to prevent further SSH authentication capabilities.

Be sure to check for any established SSH connections by the disabled user, as it is possible they may have existing inbound or outbound connections. Kill any that are found.

Restrict SSH access to only user accounts that should have it. For example, you may create a group called `sshlogin` and add the group name as the value associated with the `AllowGroups` variable located in the file `/etc/ssh/sshd_config`.

```
AllowGroups sshlogin
```

Then add your permitted SSH users to the group `sshlogin`, and restart the SSH service.

```
sudo adduser username sshlogin
sudo /etc/init.d/ssh restart
```

1.3 Creating a user account in Ubuntu with only web-surfing enabled

In many situation's, we come across a need to enable only a certain application for the guest user and we have to protect our files, directories and applications from their access. A good example is a browsing centre that provides the user just browsing facility.

What we're going to do...

Create a guest account and enable only the web browser application.

Step 1: Creating the unprivileged user account.

We can create the new unprivileged user account named guest here.

Go to **System > Administration > Users & Groups**.

Unlock the application by providing your password and click on the **Add User** button.

Fill the details like user name as guest (or anything as you wish, but don't forget to replace the following commands for the word guest), password, and select the profile as unprivileged user, and click **OK**.

Step 2: Configuring the user session.

Now we have to configure the user to run the web browser alone. For this we have to create the `xsession` configuration. Open the `xsession` file of the guest user by following command.

```
sudo gedit /home/guest/.xsession
And type the following into the file and save it.
/usr/bin/metacity &
/usr/bin/firefox
```