

```
        umount -a
        kexec -e
    else
        reboot -d -f -i
    fi
}
```

You can even use `sysv-rc-conf` (`sudo apt-get install sysv-rc-conf`) to change the enable/disable settings. Some of the services to consider disabling include:

anacron

As mentioned earlier, this subsystem periodically runs processes. You may want to disable it and move any critical services to `cron`.

atd and cron

By default, there are not `at` or `cron` jobs scheduled. If you do not need these services, then they can be disabled. Personally, I would always leave them enabled since they take relatively few resources.

apmd

This service handles power management and is intended for older systems that do not support the ACPI interface. It only monitors the battery. If you have a newer laptop (or are not using a laptop), then you probably do not need this service enabled.

acpid

The `acpid` service monitors battery levels and special laptop buttons such as screen brightness, volume control, and wireless on/off. Although intended for laptops, it can also support some desktop computers that use special keys on the keyboard (for example, a `www` button to start the browser). If you are not using a laptop and do not have special buttons on your keyboard, then you probably do not need this service.

bluez-utiles

This provides support for Bluetooth devices. If you don't have any, then this can be disabled.

dns-clean, ppp, and pppd-dns

These services are used for dynamic, dial-up connections. If you do not use `dialup`, then these can be disabled.