

```
-rwxr--r-- 1 user user 0 Jun 14 16:19 A
```

If we want to add other write & execute bit to B, the command will be:

```
user@host:/home/user$ chmod 647 B
```

```
user@host:/home/user$ ls -l B
```

```
-rw-r--rwx 1 user user 0 Jun 14 16:20 B
```

Owner	Group	Other
write	read & execute	execute
2	4+1=5	1

If we want to remove group read bit for C, the command will be:

```
user@host:/home/user$ chmod 604 C
```

```
user@host:/home/user$ ls -l C
```

```
-rw----r-- 1 user user 0 Jun 14 16:24 C
```

If we want to add read, write and execute bit to everyone for D, the command will be:

```
user@host:/home/user$ chmod 777 D
```

```
user@host:/home/user$ ls -l D
```

```
-rwxrwxrwx 1 user user 0 Jun 14 16:24 D
```

```
user@host:/home/user$
```

You can even change permissions on files that you do not have the ownership of using the **sudo** command, if you do have the root password. Be careful while using sudo, else you might mess up your system a great deal.

Example:

```
user@host:/home/user$ ls -l /usr/local/bin/XYZfile
```

```
-rw-r--r-- 1 root root 550 2010-06-13 21:53 /usr/local/bin/XYZfile
```

```
user@host:/home/user$
```

```
user@host:/home/user$ sudo chmod o+x /usr/local/bin/XYZfile
```

```
user@host:/home/user$ ls -l /usr/local/bin/XYZfile
```

```
-rw-r--r-x 1 root root 550 2010-06-13 21:54 /usr/local/bin/XYZfile
```

```
user@host:/home/user$
```

Now, if you want to change the permissions of multiple files and directories, you can do so using the **-R** option which basically means Recursive Permission change.