

mount is passed the `-a` option). This is really unnecessary as this is the default action of mount `-a` anyway.

- **noauto** - The filesystem will NOT be automatically mounted at startup, or when mount passed `-a`. You must explicitly mount the filesystem.
- **dev/nodev** - Interpret/Do not interpret character or block special devices on the file system.
- **exec / noexec** - Permit/Prevent the execution of binaries from the filesystem.
- **suid/nosuid** - Permit/Block the operation of suid, and sgid bits.
- **ro** - Mount read-only.
- **rw** - Mount read-write.
- **user** - Permit any user to mount the filesystem. This automatically implies `noexec`, `nosuid`, `nodev` unless overridden.
- **nouser** - Only permit root to mount the filesystem. This is also a default setting.
- **defaults** - Use default settings. Equivalent to `rw`, `suid`, `dev`, `exec`, `auto`, `nouser`, `async`.
- **\_netdev** - this is a network device, mount it after bringing up the network. Only valid with `fstype nfs`.

## 5.6 Dump

This field sets whether the backup utility dump will backup file system. If set to "0" file system ignored, "1" file system is backed up. Dump is seldom used and if in doubt use 0.

## 5.7 Pass (fsck order)

Fsck order is to tell fsck what order to check the file systems, if set to "0" file system is ignored. Often a source of confusion, there are only 3 options :

- 0 == do not check.
- 1 == check this partition first.
- 2 == check this partition(s) next

In practice, use "1" for your root partition, / and 2 for the rest. All partitions marked with a "2" are checked in sequence and you do not need to specify an order.

Use "0" to disable checking the file system at boot or for network shares.

You may also "tune" or set the frequency of file checks (default is every 30 mounts) but in general these checks are designed to maintain the integrity of your file system and thus you should strongly consider keeping the default settings.

## 5.8 File system specific examples

Here are a couple of basic examples for different file system types. I will use