

Note

You can also mount the usb device with:

```
mount LABEL=<label>
```

NTFS (Windows partitions):

First install ntfsprogs:

```
sudo aptitude install ntfsprogs
```

- Show label:

```
ntfslabel <device>
```

- Change label:

```
ntfslabel <device> <label>
```

Where:

<label> = your new label

<device> = your partition to label (/dev/hda1 perhaps)

- Add an entry to fstab:

```
LABEL=DATA <mount_point> ntfs(or ntfs-3g) defaults 0 0
```

Note

You can also mount the usb device with:

```
mount LABEL=<label>
```

Useful Commands

To view the contents of /etc/fstab, run the following terminal command:

```
cat /etc/fstab
```

To get a list of all the UUIDs, use one of the following two commands:

```
sudo blkid
```

```
ls -l /dev/disk/by-uuid
```

To list the drives and relevant partitions that are attached to your system,

run:

```
sudo fdisk -l
```

To mount all file systems in /etc/fstab, run:

```
sudo mount -a
```

Remember that the mount point must already exist, otherwise the entry will not mount on the filesystem. To create a new mount point, use root privileges to create the mount point. Here is the generalization and an example:

```
sudo mkdir /path/to/mountpoint
```

```
sudo mkdir /media/disk2
```