

and `ubuntu-security` to `security.ubuntu.com`

Now, in order to access a specific repository, we simply need to append the mapping name to our cache repository server, like: `repository_cache_machine:port/mapping_name`

So, for instance, we can access Ubuntu security repository through `http://repository-cache:3142/ubuntu-security`.

The `autostart` value of 1, enables the `apt-cacher`.

`AUTOSTART=1`

At this point we should restart the `apt-cacher` for our changes to take place.

```
$ sudo /etc/init.d/apt-cacher restart.
```

This was the server part of our setup, now login to each of the clients. Don't worry, you don't need to physically move, you can log in via SSH as explained earlier, or you can even write an automated script to do so. Let us update all our clients `/etc/apt/sources.list` files so every host on the network will use our repository-cache machine. It is a good idea to even update the `sources.list` on the server, as any software downloaded by the server will also be available for rest of the machines.

6.1 Editing the `sources.list`

Here is a sample original `sources.list`

```
# deb cdrom:[Ubuntu 10.04 LTS _Lucid Lynx_ - Release amd64 (20100429)]/ lucid main restricted
```

```
# See http://help.ubuntu.com/community/UpgradeNotes for how to upgrade to
```

```
# newer versions of the distribution.
```

```
deb http://lk.archive.ubuntu.com/ubuntu/ lucid main restricted
```

```
deb-src http://lk.archive.ubuntu.com/ubuntu/ lucid main restricted
```

```
## Major bug fix updates produced after the final release of the
```

```
## distribution.
```

```
deb http://lk.archive.ubuntu.com/ubuntu/ lucid-updates main restricted
```

```
deb-src http://lk.archive.ubuntu.com/ubuntu/ lucid-updates main restricted
```

```
## N.B. software from this repository is ENTIRELY
```