

A directory containing local configuration directives for Apache2, such as those associated with third-party or locally installed packages.

`/etc/apache2/envvars`

A file containing environment variables that you want to set in the environment used by the `apache2ctl` script to manage an Apache 2 Web server.

`/etc/apache2/mods-available`

A directory containing available Apache 2 modules and their configuration files.

`/etc/apache2/mods-enabled`

A directory containing symbolic links to actively enable Apache 2 modules and their configuration files, located in the `/etc/apache2/mods-available` directory. This is analogous to the use of symbolic links to start various processes from the scripts in `/etc/init.d` at different run levels.

`/etc/apache2/sites-available`

A directory containing files that define the web sites supported by this server.

`/etc/apache2/mods-enabled`

A directory containing symbolic links to actively enabled

Web sites for this server, located in the `/etc/apache2/mods-available` directory. This is analogous to the use of symbolic links to start various processes from the scripts in `/etc/init.d` at different run levels.

`/etc/default/apache2`

A configuration file that determines whether the Apache 2 should automatically start at boot time.

`/etc/init.d/apache2`

A shell script that uses the `apache2ctl` utility to start and stop an Apache 2 web server.

`/etc/mime.types`

The default MIME (Multipurpose Internet Mail Extensions) file types and the extensions that they are associated with.

`/usr/lib/cgi-bin`