

The location in which any CGI-BIN (Common Gateway Interface scripts) for a default Apache 2 Web server will be installed.

/usr/sbin/apache2

The actual executable for the Apache 2 Web server.

/usr/sbin/apache2ctl

An administrative shell script that simplifies starting, stopping, restarting, and monitoring the status of a running Apache 2 Web server.

/usr/share/apache2-doc

A directory that contains the actual Apache 2 manual (in the manual subdirectory). This directory is present only if you've installed the apache2-doc package (as suggested earlier).

/usr/share/apache2/error

A directory containing the default error responses delivered.

/usr/share/apache2/icons

A directory containing the default set of icons used by an Apache 2 Web server. This directory is mapped to the **/icons** directory in your Apache server's primary configuration file.

/var/log/apache2/access.log

The default access log file for an Apache 2 Web server. This log file tracks any attempts to access this web site, the hosts that they came from, and so on.

/var/log/apache2/error.log

The default error log file for an Apache 2 Web server. This log file tracks internal Web server problems, attempts to retrieve nonexistent files, and so on.

/var/run/apache2/apache2.pid

A text file used by Apache 2 to record its process ID when it starts. This file is used when terminating or restarting the Apache 2 server using the **/etc/init.d/apache2** script.

/var/www/apache2-default

A directory containing the default home page for this Web server. Note that the default Apache 2 Web server does not display the content of this directory correctly.

You will be able to access the default Apache webpage at **http://localhost/**.