

The main configuration file is located at `/etc/apache2/apache.conf`. Default document root for apache2 is `/var/www`. This means you need to put the files that you want Apache to serve in `/var/www`. If you want to change the default document root, you need to edit the `/etc/apache2/sites-available/default` file and look for this line `DocumentRoot /var/www/`. Here you can change where ever you want to change. For example, if you want to change `/home/www` the above line looks like this `DocumentRoot /home/www/`. All the configuration options are well documented and you need to restart the apache daemon whenever you change the config file

```
$ sudo /etc/init.d/apache2 restart
```

7.4 LAMP

If you want to get MySQL and PHP support for apache, the easiest way is to install LAMP:

```
$ sudo apt-get install lamp-server^
```

The ^ is not a typo.

After the packages get downloaded and installed, you will be asked to change the root user's password on the MySQL database. After this, the rest of the packages get installed. Now you need to test if all the components are working.

7.5 Testing Apache

Access <http://localhost/> from a browser. You should see a web page that says It Works!

7.6 Testing PHP

First create a simple php file in `/var/www` :

```
$ sudo echo "<?php phpinfo(); ?>" > /var/www/test.php
```

and restart apache

```
$ sudo /etc/init.d/apache2 restart
```

Now navigate to <http://localhost/test.php/>. You should see a page describing version information for your php installation.

7.7 Installing PhpMyAdmin

phpMyAdmin is not essential, but it is a much simpler way to get in and adjust things in your MySQL database if you are not familiar with MySQL's commands. You can install phpMyAdmin using apt-get:

```
$ sudo apt-get install libapache2-mod-auth-mysql phpmyadmin
```

The installation will ask you to select a webserver for automatic configuration. Make sure you choose apache2. Follow the installer and it