

blocked by spam blockers. And it is more work for your server. Also many servers block dynamic dns hosts, so you may find your server gets rejected. However choose whichever you are suits your needs better

```
# leave blank to do it yourself relayhost =  
# or put it an accessible smtp server  
relayhost = smtp.externalserver.com
```

Next is network details. You will accept connection from anywhere, and you only trust this machine `inet_interfaces = all`

```
mynetworks_style = host
```

Next you can masquerade some outgoing addresses. Say your machine's name is `mail.domain.com`. You may not want outgoing mail to come from `username@mail.example.com`, as you'd prefer `username@example.com`. You can also state which domain not to masquerade. E.g. if you use a dynamic dns service, then your server address will be a subdomain. You can also specify which users not to masquerade.

```
# masquerade_domains = mail.example.com !www.example.  
comsub.dyndomain.com  
# masquerade_exceptions = root
```

As we will be using virtual domains, these need to be empty.

```
local_recipient_maps =  
mydestination =
```

Then will set a few numbers.

```
# how long if undelivered before sending warning update  
to sender
```

```
delay_warning_time = 4h  
# will it be a permanent error or temporary  
unknown_local_recipient_reject_code = 450
```

```
# how long to keep message on queue before return as  
failed.
```

```
maximal_queue_lifetime = 7d
```

```
# max and min time in seconds between retries if  
connection failed
```

```
minimal_backoff_time = 1000s maximal_backoff_time =  
8000s
```

```
# how long to wait when servers connect before receiving  
rest of data
```

```
smtp_helo_timeout = 60s
```

```
# how many address can be used in one message.
```