

```
# effective stopper to mass spammers, accidental copy
in whole address list
# but may restrict intentional mail shots.
smtpd_recipient_limit = 16
# how many error before back off.
smtpd_soft_error_limit = 3
# how many max errors before blocking it.
smtpd_hard_error_limit = 12
```

Now we can specify some restrictions. Be carefull that each setting is on one line only.

```
# Requirements for the HELO statement
smtpd_helo_restrictions = permit_mynetworks, warn_if_
reject reject_non_fqdn_hostname, reject_invalid_hostname,
permit
# Requirements for the sender details
smtpd_sender_restrictions = permit_mynetworks, warn_
if_reject reject_non_fqdn_sender, reject_unknown_sender_
domain, reject_unauth_pipelining, permit
# Requirements for the connecting server smtpd_client_
restrictions = reject_rbl_client sbl.spamhaus.org, reject_
rbl_client blackholes.easynet.nl, reject_rbl_client dnsbl.
njabl.org
# Requirement for the recipient address
smtpd_recipient_restrictions = reject_unauth_pipelining,
permit_mynetworks, reject_non_fqdn_recipient, reject_
unknown_recipient_domain, reject_unauth_destination,
permit smtpd_data_restrictions = reject_unauth_pipelining
```

Further restrictions:

```
# require proper helo at connections
smtpd_helo_required = yes
# waste spammers time before rejecting them
smtpd_delay_reject = yes
disable_vrfy_command = yes
```

Next we need to set some maps and lookups for the virtual domains.

```
alias_maps = hash:/etc/postfix/aliases
alias_database = hash:/etc/postfix/aliases
# this specifies where the virtual mailbox folders will
be located
virtual_mailbox_base = /var/spool/mail/virtual # this is
```