

```
for the mailbox location for each user virtual_mailbox_
maps = mysql:/etc/postfix/mysql_mailbox.cf # and this
is for aliases virtual_alias_maps = mysql:/etc/postfix/
mysql_alias.cf # and this is for domain lookups virtual_
mailbox_domains = mysql:/etc/postfix/mysql_domains.cf
# this is how to connect to the domains (all virtual,
but the option is there)
# not used yet #
transport_maps = mysql:/etc/postfix/mysql_transport.cf
```

You can use a lookup for the uid and gid of the owner of mail files.

```
virtual_uid_maps = static:5000 virtual_gid_maps =
static:5000
```

You need to set up an alias file. This is only used locally, and not by your own mail domains.

```
$ sudo cp /etc/aliases /etc/postfix/aliases
# may want to view the file to check if ok.
# especially that the final alias, eg root goes
# to a real person
$ sudo postalias /etc/postfix/aliases
```

Next you need to set up the folder where the virtual mail will be stored. This may have already been done by the apt-get. And also create the user who will own the folders.

```
# to add if there is not a virtual user
sudo mkdir /var/spool/mail/virtual
sudo groupadd --system virtual -g 5000
sudo useradd --system virtual -u 5000 -g 5000
sudo chown -R virtual:virtual /var/spool/mail/virtual
```

7.11 Postfix's MySQL configuration

Next we need to set up the files to access the lookups via the database. We will only set up a few now, and the rest later when/if needed:

Edit or create `mysql_mailbox.cf` which tells postfix how to find the users mailbox location

```
$ sudo gedit /etc/postfix/mysql_mailbox.cf
user=mail
password=mailPASSWORD
dbname=maildb
table=users
select_field=maildir
where_field=id hosts=127.0.0.1
```