

```
additional_conditions = and enabled = 1
```

Create the file which tells postfix how to find the email alias:

```
$ sudo gedit /etc/postfix/mysql_alias.cf
user=mail password=mailPASSWORD
dbname=maildb
table=aliases select_field=destination
where_field=mail hosts=127.0.0.1 additional_conditions
= and enabled = 1
```

Create the file which tells postfix how to find the domains:

```
$ sudo gedit /etc/postfix/mysql_domains.cf
user=mail password=mailPASSWORD
dbname=maildb
table=domains
select_field=domain where_field=domain
hosts=127.0.0.1 additional_conditions = and enabled = 1
```

If you specify an IP in hosts, (as opposed to 'localhost') then it will communicate over tcp and not the mysql socket due to a **chroot** restriction. Don't forget to replace the passwords with your chosen mail user password.

7.12 Database

MySQL

Now we will need to create the tables for thos lookups just specified. First you need to create a user to use in MySQL for mail only. Then you need to create the database, Take note of your chosen mail username and password. You will need the password you specified for root during MySQL package installation.

```
# If not already done (in package installation or
previous configuration)...
mysqladmin -u root password new_password
# log in as root mysql -u root -p
# then enter password for the root account when prompted
Enter password:
# then we create the mail database create database
maildb;
# then we create a new user: "mail"
GRANT SELECT,INSERT,UPDATE,DELETE,CREATE,DROP ON maildb.*
TO 'mail'@'localhost' IDENTIFIED by 'mailPASSWORD';
GRANT SELECT,INSERT,UPDATE,DELETE,CREATE,DROP ON
```