

```
maildb.* TO 'mail'@'%' IDENTIFIED by 'mailPASSWORD'; exit;
```

Replace mailPASSWORD with your chosen password.

Then you will need to create these tables:

aliases

domains

users

You will need to create more later on for the extensions, but only these are relevant now.

Log in to mysql as the new mail user

```
mysql -u mail -p maildb
```

enter the newly created password

Enter password:

Then run this commands to create the tables:

```
CREATE TABLE `aliases` (
  `pkid` smallint(3) NOT NULL auto_increment,
  `mail` varchar(120) NOT NULL default '',
  `destination` varchar(120) NOT NULL default '',
  `enabled` tinyint(1) NOT NULL default '1',
  PRIMARY KEY (`pkid`),
  UNIQUE KEY `mail` (`mail`)
) ;
```

```
CREATE TABLE `domains` (
  `pkid` smallint(6) NOT NULL auto_increment,
  `domain` varchar(120) NOT NULL default '',
  `transport` varchar(120) NOT NULL default 'virtual:',
  `enabled` tinyint(1) NOT NULL default '1',
  PRIMARY KEY (`pkid`)
) ;
```

```
CREATE TABLE `users` (
  `id` varchar(128) NOT NULL default '',
  `name` varchar(128) NOT NULL default '',
  `uid` smallint(5) unsigned NOT NULL default '5000',
  `gid` smallint(5) unsigned NOT NULL default '5000',
  `home` varchar(255) NOT NULL default '/var/spool/mail/
virtual',
  `maildir` varchar(255) NOT NULL default 'blah/',
  `enabled` tinyint(3) unsigned NOT NULL default '1',
  `change_password` tinyint(3) unsigned NOT NULL default
```