

```
'1', `clear` varchar(128) NOT NULL default 'ChangeMe',
`crypt` varchar(128) NOT NULL default 'sdtrusfX0Jj66',
`quota` varchar(255) NOT NULL default '', `procmailrc`
varchar(128) NOT NULL default '', `spamassassinrc`
varchar(128) NOT NULL default '', PRIMARY KEY (`id`),
UNIQUE KEY `id` (`id`) );
```

The last few fields in the users table are not required, but useful if you extend later.

To visualise the tables created: describe aliases; describe domains; describe users; # then quit mysql exit;

Next, edit the MySQL's my.cnf file. In Ubuntu/Debian this is created by default. In Mandrake we had to manually create a blank one in /etc. But we need to configure it, so: `sudo vi /etc/mysql/my.cnf`. In previous version you needed to comment out this line `#skip-networking` However in todays file the default is to bind the address to localhost, which is fine. `bind-address = 127.0.0.1`. It is very useful at the start to log any SQL calls that makes it to MySQL. So enable these lines: `general_log_file = /var/log/mysql/mysql.log` `general_log = 1`. Then in a few weeks comment it out when everything is working, as it slows mysql down

Restart MySQL to make sure its picking up the new settings. `sudo /etc/init.d/mysql restart`

Return to top.

Pop/IMAP

Courier IMAP

```
$ sudo gedit /etc/courier/authdaemonrc
```

Change to mysql mode.

```
authmodulelist="authmysql"
```

Further down enable logging.

```
DEBUG_LOGIN=2
```

```
sudo gedit /etc/courier/authmysqlrc
```

```
MYSQL_USERNAME mail
```

Change the password to whichever you have chosen

```
MYSQL_PASSWORD mailPASSWORD
```

```
MYSQL_DATABASE maildb
```

```
MYSQL_USER_TABLE users
```

```
MYSQL_CRYPT_PWFIELD crypt
```

```
# MYSQL_CLEAR_PWFIELD clear
```

```
MYSQL_MAILDIR_FIELD concat(home, '/', maildir)
```

```
MYSQL_WHERE_CLAUSE enabled=1
```

Lastly you can have a look at the imapd file, but no changes is needed. It is located in /etc/courier/imapd