

### 7.13 Antispam

The default config of spam assassin is ok. But you need to tell SpamAssassin to start smapd at boot.

```
$ sudo gedit /etc/default/spamassassin.
```

You can also enable Bayes and auto learning by editing `/etc/spamassassin/local.cf`

### 7.14 Antivirus

ClamAV has sensible defaults except the fact that it updates 24 times a day, If you want to change that edit the configuration file in `/etc/clamav`.

### 7.15 PostGrey

Postgrey has a good default configuration but you need to tell Postfix to use it.

Edit postfix's main config:

```
$ sudo gedit /etc/postfix/main.cf
```

And then edit the recipient restrictions:

```
smtpd_recipient_restrictions = reject_unauth_
pipelining, permit_mynetworks, permit_sasl_authenticated,
reject_non_fqdn_recipient, reject_unknown_recipient_
domain, reject_unauth_destination, check_policy_service
inet:127.0.0.1:10023, permit
```

You can tweak options such as delay and auto whitelisting and reject message in `/etc/default/postgrey`.

### 7.16 Webmail

This tutorial shows you how to set up squirrelmail instead of roundcube because roundcube is still in beta.

To run Squirrelmails configuration utility run:

```
$ sudo squirrelmail-configure
```

You need to configure apache now, run this command:

```
$ sudo a2ensite squirrelmail
```

then reload apache configuration:

```
$ sudo /etc/init.d/apache2 force-reload
```

Now your mail server is almost setup, you still need to add users and domains.

Before adding your own users and domains, you need to add some required default data.

Use phpMyAdmin or command line mysql to do this: