

```
top:82px;
right:10px;
width:30%;
margin-bottom:10px;
padding:10px;
border:1px solid #000;
}
```

Note that `right:10px` is also specified to ensure that the sidebar does not push up against the right edge of the browser window, and therefore honours the 10 pixels of padding around the `<body>` element.

This approach has a hidden problem. Once the sidebar contains more elements the sidebar overlaps the footer. Remember that with a floated sidebar, the footer could be cleared to ensure it began after the columns. With positioning, however, the sidebar has been taken out of the normal flow of elements, and the footer can't "see" this. The best approach here is to make the footer work like the content ID, by giving it a right margin and thus creating space for the sidebar.

```
/* Footer */
#footer {
margin-right:40%;
padding:10px;
border:1px solid #000;
background-color:#CCC;
}
```

The footer no longer stretches the full width of the layout. Another problem is that the greater the difference in amount of content between content ID and sidebar ID, the more unbalanced the layout will look.

9.7 Liquid positioned three-column layout

Moving from two columns to three using the positioning method isn't too difficult. Remember how we adjusted the right margin of the main content ID to allow space for a sidebar? Well, all we have to do is something similar with the left margin. First of all, sidebar is removed, and two new sidebars need to be added to the markup. They can be placed anywhere, seeing as CSS positioning will be used to place them visually. To stay semantic, let's add them after the content ID. Again, these changes can be made to the `columns.html` file.