

3. Create another style sheet called `layout.css`.
4. Place the following CSS into `layout.css`: `#header {height: 100px; width: 100%; border: 1px solid #999;}`; and save the file.
5. Open `external.css` and replace the existing CSS with the following:
`@import url("default.css");`
`@import url("layout.css");`
6. Save the file.
7. Open `external.html` and ensure the link to `external.css` is still in place.
8. Find `<h1>Applying CSS Templates</h1>` and wrap this with the hooks for the header, so you end up with `<div id="header"><h1>Applying CSS Templates</h1></div>`
9. Save `external.html` and view it in your browser.

Notice that the CSS from `default.css` is still giving you a red paragraph, but also that the header rule from `layout.css` is placing a box of 100 pixels height by 100 pixels width around the heading text. The `external.css` file is successfully combining the two style sheets it imports for a complete effect.

1.6.4 Commenting

Defining rules is just the beginning. Consider how unmanageable a style sheet can become once it holds 20 or 30 rules. This is where commenting becomes invaluable. The following example includes simple comments that remind us what the rules are there for:

```
/* Default styling for paragraphs */
p {
  color: #F00;
  font-size: 12px;
}
/* Make all top-level headings gray and 16px high */
h1 {
  color: #333;
  font-size: 16px;
}
```

Introducing comments into style sheet makes things easier for any changes you would need to do later or if someone other than you has to work with the same code. It explains what your rule is supposed to be doing and is a good practice. All comments begin with a forward slash and asterisk (`/*`), and end with the asterisk followed by the forward slash (`*/`).